Telo TE580

by Logic Wireless



Smart LTE Handheld

Delivers an exceptional combination of rugged hardware, powerful software and broadband connectivity.



TE580 rugged Push To Talk over Cellular (PTToC) LTE device for mobile workforce voice, text and location services

TE580 Features

- Supports GSM, 3G, 4G/LTE bands 1, 3, 5, 7, 8, 20, 28
- ChatterPTT push-to-talk client pre-installed
- Android 5.1 allows other applications to be installed (*)
- · Bluetooth, WiFi and GPS built in
- 2.4" capacitive touch screen
- SOS / Emergency key to enhance worker safety
- Audio interface fits a variety of traditional two-way radio accessories
- Removable high-capacity battery. Spare batteries available
- 2W speaker provides loud, clear voice
- Expandable SD memory card slot
- IP67 rating to withstand dust, rain and water immersion of 1 meter for 30 minutes

(*) Requires Google Play Store account. Application lockout also available to prevent unauthorised users installing applications.



ChatterPTT app included

The TE580 comes pre-installed with ChatterPTT, a premium mobile app and gateway PTToC solution to communicate seamlessly, across multiple devices.

ChatterPTT intelligently enables different types of communication devices, such as two-way radios and smart phones, to communicate directly with each other. Regardless of their device, network or location, your team can connect instantly as a group or one-to-one.

















Worker Safety and Business Efficiency

- Safety in numbers. Communicate voice, messages or images with the whole team.
- Keep it private. Sensitive calls, messages and images can be sent to individuals over the secure cellular network.
- Combining group calling and GPS location with the convenience of GSM, 3G and 4G/LTE cellular network infrastructure makes the TE580 ideal for organisations focussed on improving business efficiency and worker safety.
- No infrastructure overheads works over cellular and WiFi



Speaker Microphone

- Commercial grade
- 3.5mm earphone audio jack
- Loud, clear audio
- Textured PTT and orange emergency key
- Curly cord with heavy duty strain relief
- Rotating belt / clothing clip
- Secure attachment to TE580 it won't pull out!



Desktop Charger

- Docking slots for TE580 and spare battery
- Powered by USB
- Charging dock for home or office





In-vehicle Charger

- Machined solid acetal plastic
- Beryllium Copper wipe-action battery contact
- Installation cable with fuse holder included
- TE580 retaining strap



Audio Wire Kits

- Combined microphone and PTT module
- Separate earpiece options acoustic tube – flexible earhook D-earhanger
- Rugged Kevlar re-enforced cable and heavy-duty strain relief.



Choose your LTE network provider

- Operating on your choice of cellular network, the TE580 simply needs a SIMcard and a push-to-talk account such at ChatterPTT to be up and running in minutes.
- The device can also use WiFi networks when available to reduce operating costs.

Heavy Duty Headset (available soon)

- Certified noise reduction of 24dB
- Flexible, noise cancelling boom microphone
- Comfortable ear seals
- PTT on ear cup
- Full range of replacement parts available



Tech Specs

Connectivity

Cellular Supports GSM, 3G, 4G/LTE – bands 1, 3, 5, 7, 8, 20, 28

WiFi Operating Band: 2.4GHz and 5GHz

Standards: 802.11 a/b/g/n

Bluetooth BT 4.0 with BLE/BT2.1 +EDR (Enhanced Data Rate)

GPS GLONASS, GPS, AGPS support

Hardware

CPU ARM: Mediatek MT6735V/W

Memory RAM / ROM: 1GB / 8GB

SD Card: 32GB

Display 2.4" Capacitive touch screen

Camera Back: 8M pixels with focus

Front: 2M pixels Flash light/torch

Speaker Output: 2.0W

Battery 3,600 mAh

Ports USB type: Micro USB

Sensors G-Sensor

Software

Operating System Android 5.1

Web Browser Google Chrome / Google Play / Google Services

Push-to-talk ChatterPTT

Mapping Google Maps

Physical

Dimension 119.5 x 61.5 x 26.5 (mm)

Weight Less than 200g

Durability IP67, Drop Test 1.5m

Operating Temperature -20° C to 60° C

Storage Temperature -30° C to 70° C

