



**TeloSystems**  
Bridging Communication Gap



### OLED Screen

Intuitive display readable from multiple angles

### PTT Button

Textured surface with positive feedback



### Radio Design Interface

Powerful compatibility for radio accessories



# TeloPTT TE390

**Simplified LTE Handheld Device**

Compact, Durable, Handy

[www.telosystems.com](http://www.telosystems.com)

# TECHNICAL SPECIFICATION

| Connectivity                  |   | Specifications |
|-------------------------------|---|----------------|
| <b>Frequency Band</b>         | <b>Global Version:</b><br><b>GSM:</b> B2/B3/B5/B8 <b>WCDMA:</b> B1/B2/B5/B8 <b>TD-SCDMA:</b> B34/B39 <b>FDD-LTE:</b> B1/B3/B7/B8/B20/B28A/B28B<br><b>TDD-LTE:</b> B38/B39/B40/B41<br><br><b>American Version:</b><br><b>GSM:</b> B2/B5 <b>WCDMA:</b> B1/B2/B4/B5/B19 <b>FDD-LTE:</b> B1/B2/B4/B5/B7/B12/B17/B19/B28A/B28B |                |
| <b>WIFI</b>                   | IEEE802.11a/b/g/n(2.4G, 5G)   |                |
| <b>Bluetooth</b>              | BT v4.0 with BLE/ BT2.1+EDR(Enhanced Data Rate)   |                |
| <b>GPS</b>                    | GPS/GLONASS/AGPS  |                |
| Hardware                      |   | Specifications |
| <b>CPU</b>                    | MTK6737M  |                |
| <b>Memory</b>                 | RAM+ROM: 1GB + 8GB  |                |
| <b>Display</b>                | OLED 0.97", 128*64 RGB  |                |
| <b>Speaker</b>                | 2.0W, Ø36mm   |                |
| <b>Battery</b>                | Li-Po 3600mAh   |                |
| <b>USB Port</b>               | Micro USB2.0  |                |
| <b>Interface</b>              | M6 Interface for Remote Speaker Microphone, Earpiece  |                |
| <b>Sensor</b>                 | 3D Gravity Sensor, Acceleration Sensor  |                |
| Software                      |   | Specifications |
| <b>Operation System</b>       | Android 5.1   |                |
| Physical                      |   | Specifications |
| <b>Dimensions (H x W x D)</b> | 117*60*29.2mm   |                |
| <b>Weight</b>                 | 182g  |                |
| <b>Protection Rating</b>      | IP67, 1.5m drop test  |                |
| <b>Working Temperature</b>    | -20°C ~ 60°C  |                |
| <b>Storage Temperature</b>    | -30°C ~ 70°C  |                |



For more information contact:



+61 3 9024 9400 [www.datalinktech.com.au](http://www.datalinktech.com.au)